

## Mini Electric Pallet Truck **CEY15A**

- ◆ Capacity:1500kg, DC power,light-duty conditions.
- ◆ Fit for small work space,double-side pallet can use.
- ◆ Maintenance-free battery/easy replance/inner charger.
- ◆ Replace hand pallet truck, load/unload on vehicles.
- ◆ Low voltage protection, truck will stop if voltage is lower, make truck/battery with long using life.
- ◆ Emergency stop/hour meter/Battery level indicator.



Model		CEY15A
Load Capacity	(kg)	1500
Load Center	(mm)	600
Wheel Base	(mm)	1301
Operating Type		Walkie
Wheels Type		PU
Wheel Quantity Driving Wheel / Balance Wheel / Bearing Wheel		1/0/4
Driving Wheel Size	(mm)	Ø252×67
Balance Wheel Size	(mm)	Ø84×70
Bearing Wheel Size	(mm)	-
Min. Fork Lowered Height		85
Max. Fork Lifting Height	(mm)	205
Max. Lifting Height	(mm)	120
Outside Width between Forks	(mm)	550/685
Inside Width between Forks		230/365
Fork Length	(mm)	1150/1200
Fork Width	(mm)	160
Fork Thickness	(mm)	55
Overall Length	(mm)	1707
Overall Width	(mm)	697
Overall Height(With handle)	(mm)	1181
Overall Height(Without handle)	(mm)	714
Min. Turning Radius	(mm)	1547
Min. Aisle Width for Pallets 800×1200	(mm)	1920
Min. Aisle Width for Pallets 1000 ×1200	(mm)	1953
Travelling Speed (laden / unladen)	(km/h)	3/3.5
Lifting Speed (laden / unladen)	(mm/s)	56/60
Lowering Speed (laden / unladen)	(mm/s)	57/59
Gradeability (laden / unladen)	(%)	5/7
Driving Motor	(KW)	DC 0.63
Lifting Motor	(KW)	DC 0.8
Battery Voltage / Capacity	(V/Ah)	24/70
Brake		Electromagnetic / Regenerative
Battery Weight	(kg)	48
Service Weight with Battery	(kg)	275

## Mini Electric Pallet Truck **CEY15B**

- ◆ Capacity:1500kg, DC power,light-duty conditions.
- ◆ Fit for small work space,double-side pallet can use.
- ◆ Maintenance-free battery/easy replance/inner charger.
- ◆ Replace hand pallet truck, load/unload on vehicles.
- ◆ Low voltage protection, truck will stop if voltage is lower, make truck/battery with long using life.
- ◆ Emergency stop/hour meter/Battery level indicator.



Model		CEY15B
Load Capacity	(kg)	1500
Load Center	(mm)	600
Wheel Base	(mm)	1285/1235
Wheels Type		PU
Wheel Quantity Driving Wheel / Balance Wheel / Bearing Wheel		1/0/4
Driving Wheel Size		Φ210×70
Balance Wheel Size	(mm)	Ø84×70 Double Ø80×101 Single
Min. Fork Lowered Height	(mm)	85
Max. Fork Lifting Height	(mm)	205
Max. Lifting Height		120
Outside Width between Forks	(mm)	550
Inside Width between Forks	(mm)	390
Fork Length	(mm)	1150/1200
Fork Width		160
Fork Thickness	(mm)	73
Overall Length	(mm)	1648/1698
Overall Width	(mm)	570
Overall Height(With handle)	(mm)	1213
Overall Height(Without handle)	(mm)	634
Min. Turning Radius	(mm)	1414/1464
Min. Aisle Width for Pallets 800×1200	(mm)	1728/1778
Min. Aisle Width for Pallets 1000×1200	(mm)	1764/1814
Travelling Speed (laden / unladen)	(km/h)	3.5/4
Lifting Speed (laden / unladen)	(mm/s)	20/25
Lowering Speed (laden / unladen)	(mm/s)	40/30
Gradeability (laden / unladen)	(%)	5/7
Driving Motor	(KW)	DC0.65
Lifting Motor	(KW)	DC0.8
Steering Motor	(KW)	-
Battery Voltage / Capacity	(V/Ah)	24V/65Ah
Brake		Electromagnetic
Battery Weight	(kg)	100
Service Weight with Battery	(kg)	210